

CUSTOM INDICATORS FOR THE HELICYCLE (Revised 5/31/2022)		
Item #	Description	Price
1	<b>3 1/8" AIRSPEED 20-120 MPH W/ MARKINGS - 16-310-122</b> MKGS: GA 20-100, YA 100-110, RA 110-120 MPH (Custom markings for the Helicycle)	\$331.25
2	<b>3 1/8" VERTICAL SPEED, 0-2000 FT/MIN B&amp;W - 8-310-20</b> (This is a stock indicator)	331.25
3	<b>2 1/4" OPTI-ALERT EGT, 400-1300F W/ MKGS (TYPE K PROBE) - N12267K1K3F010</b> MKGS: GA 400-1100, YA 1100-1180, RR@ 1180F. HIGH RED WARNING LED & WIRING FOR EXTERNAL ALARM SET PT: 1150F & ABOVE. (Custom markings for the Solar T62T-32 engine including red line alarm and internal LED)	\$337.50
4	<b>2-1/4" OPTI-ALERT FUEL FLOW: 4-18 GAL/HR W/MKGS, GA 4-15, YA 15-15.9, RA 15.9-18 GPH</b> RED LED & EXT ALARM SET PT @ 15.9 GPH & ABOVE ( <b>FT-60 transducer required</b> ) (Custom markings for the Helicycle with high flow alarm) - <b>N20262E4180010</b>	\$330.00
5	<b>FUEL FLOW TRANSDUCER: ELECTRONICS INTERNATIONAL FT-60 - FITTINGS: 1/4" FEMALE NTP,</b> FLOW RATE: 0.6 - +70 GPH	\$205.00
6	<b>2 1/4" OPTI-ALERT FUEL QTY, E-F, (5V CAP SENDER) W/ LED - N1826251C1000</b> B&W. LOW RED LED WARNING LIGHT & EXT WIRING SET POINT @ 1/4 & BELOW ( <b>Westach fuel quantity probe required</b> )	\$271.25
7	<b>1 1/4" ENG.OIL TEMP 40-300F W/ MKS &amp; EXT. WARNING WIRE - N1216EU430F010</b> (REQUIRES 5K OHM THERMISTOR PROBE). MKGS: GA 100-170, YA 170-180, RA 180-300F. EXT'L HIGH WARNING WIRE: SET PT@ 180F & ABOVE (Custom markings for the Helicycle with high temp alarm)	\$320.00
8	<b>1/8-NPT(27) BAYONET 5K OHM THERMISTOR TEMP PROBE - 1B1</b> (Temperature probe for above)	\$85.00
9	<b>1 1/4" TRAN.OIL TEMP 40-300F W/ MKS &amp; EXT. WARNING WIRE -N1216FU430F010</b> (REQUIRES 5K OHM THERMISTOR PROBE). MKGS: GA 100-200, YA 200-235, RA 235-300F. EXT'L HIGH WARNING WIRE: SET PT@ 235F & ABOVE (Custom markings for the Helicycle with high temp alarm)	\$320.00
10	<b>1/8-NPT(27) BAYONET 5K OHM THERMISTOR TEMP PROBE - 1B1</b> (Temperature probe for above)	\$85.00
11	<b>1 1/4" ENG. OIL PRESS, 0-60 PSI W/ MKS &amp; EXT. WARNING WIRE - N0416E5060P010</b> (60 PSI/ .5-4.5V OUTPUT SENDER REQ'D). MKGS: GA 25-40, YA 15-25 & 40-50, RA 0-15 & 50-60 PSI. EXTERNAL ALARM WIRING: LOW SET POINT@ 15 PSI & BELOW/ HIGH SET PT@ 50 PSI & ABOVE. (Custom Engine Oil Pressure For the T62T-32 engine with high and low pressure alarms)	\$370.00
12	<b>UMA CERAMIC PRESS SENDER 60 PSI ; 0.5-4.5V OUTPUT - N3EUMA060G-A02</b> 1/8 MNPT PORT, 2' LEAD (Oil Pressure sensor for above)	\$153.75

13	<b>1 1/4" VOLTMETER</b> , 9-17V W/ MKGS & EXT'L WARNING WIRING - <b>N141600917V0B0</b>	\$357.50
	MKGS: GA 12-14.4, YA 11-12 & 14.4-15, RR@ 9-11 & 15-17V. EXT. ALARM	
	WIRING SET POINTS: LOW WARNING@ 11V & BELOW/ HIGH WARNING@ 15V ABOVE	
	(Custom Expanded scale voltmeter with high and low voltage alarms)	
14	<b>1 1/4" AMMETER</b> W/DB-9 CONN.; (-30/0/+30); INCLUDES SHUNT, B&W - <b>N15110003CA000</b>	\$256.25
	UMA 30 AMP (50 mV) SHUNT INCLUDED	
	(This is a stock indicator completewith shunt) - <b>1CU1</b>	
15	<b>1 1/4" FUEL PRESSURE</b> 0-15 PSI, MKG & EXT. WARNG WIRE - <b>N041625015P010</b>	\$295.00
	MKGS: RA 0-4, GA 4-15 PSI EXTERNAL ALARM WIRING	
	(PIN#7) : LOW SET POINT@ 4PSI & BELOW.	
16	<b>UMA CERAMIC PRESS SENDER</b> 15 PSI ; 0.5-4.5V OUTPUT - <b>N3EUMA15G-A02</b>	\$153.75
	1/8 MNPT PORT, 2' LEAD	
	(Oil Pressure sensor for above)	